

This product is not classified as hazardous according to the Safe Work Australia and NOHSC guidelines.

1. IDENTIFICATION OF MATERIAL AND SUPPLIER

Product Name Euromix® Flex
 Product Code PAINTFLXM
 Material Use Internal and external waterproof decorative coating for walls, columns & partitioning. Ideal for surfaces subjected to high winds & salt spray.
 Appearance White coloured viscous gritty liquid
 Supplier **Euroset Manufacturing Pty Ltd**
 Address **13 / 65 Elizabeth Street**
 Wetherill Park NSW 2164
 Telephone **(02) 9002 5820**
 Fax **(02) 9002 5824**
 Email **admin@euromix.com.au**

2. HAZARD IDENTIFICATION

Dangerous Goods Class/Subsidiary Risk	None allocated
Hazchem Code	None allocated
Poisons Schedule Number	None allocated

3. MATERIAL COMPOSITION

Chemical Name	CAS number	Proportion
Water	7732-18-5	>20%
Polymer	Proprietary	>50%
Inert Fillers	N/A	<35%
Other	N/A	<10%

4. FIRST AID

Swallowed	Do not induce vomiting. Give plenty of water to drink. Rinse out mouth. Seek medical assistance or contact the Poisons information Service (Australia 121 126 and New Zealand 03 4747 000).
Eyes	Flush thoroughly with clean water, holding eye lid open to flush product from under the lid. Removal of contact lens after injury should be done by a skilled or medical person.
Skin	Remove contaminated clothing, and wash with soap and water.
Inhaled	Product is water based. Treat as for drowning. Remove person to fresh air and perform artificial respiration if required and seek urgent medical assistance. If fumes are inhaled, remove to fresh air, lay patient down, keep warm and rested. This is usually sufficient.
First Aid Facilities	Eye-wash station.
Notes to Doctor	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Specific Hazards	Non-combustible material
Fire Fighting Advice	Non-combustible material
Extinguishing Media	Non-combustible material

6. ACCIDENTAL RELEASE MEASURES

Dispose of as trade waste in accordance with site and local authority guidelines. Keep out of sewer and storm water drains.

7. HANDLING AND STORAGE

Handling	Euromix® Flex is supplied in 15 litre plastic buckets. Recognised local safe lifting methods should be used when lifting buckets. Avoid repeated skin contact with both dry powder and the wet mixture.
Storage / Transport	Drivers of trucks and forklifts transporting Euromix® Flex should ensure that the buckets are properly restrained. Store in cool, dry area and place out of the reach of children. Product is not flammable. Avoid freezing. Suitable containers: Plastic pails recommended by manufacturer.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls	Keep exposure to dust as low as practicable, to minimize health problems such as skin, eye and respiratory irritation. Avoid repeated skin contact with both the dry powder and the wet mixture.
Personal Protection	Recommended use of face mask and goggles (against splashes). The use of rubber or PVC gloves, coveralls and industrial footwear are also recommended. Do not use solvent to clean the skin.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point / Melting Point	+/- 100°C – as for water
Vapour Pressure	Not applicable
Specific Gravity	1.05 – 1.1
Flashpoint	Not applicable (Water based)
Flammability Limits	Not applicable (Water based)
Solubility in Water	Miscible

10. STABILITY AND REACTIVITY

Thermal decomposition: No decomposition if used correctly.

11. TOXICOLOGICAL INFORMATION

Ingestion	Material is regarded as low oral toxicity and swallowing is unlikely. Irritating, possible nausea - will affect digestive tract if swallowed in volume with abdominal irritation, pain, and vomiting.
Eye Contact	Irritation and discomfort and may cause mild temporary redness of the conjunctiva, temporary vision impairment and damage. Prolonged contact may damage eye, possibly long term.
Skin Contact	Mildly irritating. May affect skin with prolonged contact such as dermatitis. Avoid exposure to skin that is cut, damaged or irritated.
Inhalation	Irritating - may cause nausea with prolonged contact. Inhalation unlikely due to viscosity and non volatility of the product. Vapours (predominantly water) may occur at higher than normal temperatures. If affected by inhaled dust remove the operator from the dusty area to fresh air. If symptoms persist, seek medical attention. The International Agency for research on cancer (IARC) has classified "Crystalline Silica" (quartz or cristobalite) as a Group 1 - Confirmed Human Carcinogen. Studies have shown that smoking increases the risk of occupational respiratory diseases including those associated with exposure to crystalline silica. It is recommended that all storage and work areas should be smoke-free zones.

12. ECOLOGICAL INFORMATION

Collect dust and waste in containers and dispose of as trade waste in accordance with local authority guidelines. Do not dispose of in sewer and storm water drains.

13. DISPOSAL CONSIDERATIONS

Refer to Waste Management Authority and Building Site Management for local disposal guidelines.

14. TRANSPORT INFORMATION

Road and Rail	Not classified under criteria of the Australian Dangerous Goods Code (ADG Code).
Marine	Not classified under criteria of the International Maritime Dangerous Goods Code (IMDG Code).
Air	Not classified as under criteria of the International Air Transport Association (IATA) Dangerous Goods Regulation.

15. REGULATORY INFORMATION

The material is not subject to special labeling, it should be handled in accordance with good hygiene and safety practice.

16. OTHER INFORMATION

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances.

Users must, prior to usage, assess and control the risks arising from its use of the material as Euroset Manufacturing cannot anticipate or control the conditions under which the product may be used.

For further information users should contact Euroset, via the contact details listed in Section 1 on Page 1 of this MSDS.

Euroset Manufacturing Pty Ltd responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

17. CONTACT POINT

Supplier	Euroset Manufacturing Pty Ltd
Address	13 / 65 Elizabeth Street Wetherill Park NSW 2164
Telephone	(02) 9002 5820
Fax	(02) 9002 5824
Email	admin@euromix.com.au